

# **6000 PROFIELD TRACTOR CLASS**

All Vehicles Must Conform to  
“General Vehicle Rules”

1. Weight Class:  
6000 lbs. – all tractors turbo and naturally aspirated

## **NO TOLERANCE OVER 6000 LBS WILL BE ALLOWED**

3000 RPM limit with 1% tolerance

No RPM limit on naturally aspirated tractors

Naturally, aspirated gasoline tractors may run one (1) 4-barrel carburetor.  
Will allow gas turbocharged motors with 361 cu in or less to run mechanical fuel injection, NO electronic fuel injection.

18.4 x 38 maximum tire size

## **NO TOLERANCE WILL BE ALLOWED ON TIRE SIZE**

A 361 cubic inch limit on turbo tractors, 650 cubic inch maximum limit on naturally aspirated tractors

Must run a minimum of a two (2) bar cage  
Sheet metal needs to be in the family of the tractor.

Any ag motor with like brand ag rear-ends.

2. All tractors will be equipped with a five-point harness and have a roll cage. (see General Rules)
3. Tractors with tires other than sizes listed above will have their tires measured across the lugs with a tape measure to determine if they are legal.
4. Turbo and non-turbo tractors run in the same weight class.
5. Diesel powered tractors can run any injection pump. Maximum size of a P Pump. No computerized injection systems.
6. No Predator carburetors allowed.
7. Water Injection is allowed.
8. Weights must be secured to the tractor. Rear weights must not be more than 3” maximum behind rear tires. Tractor length is not to exceed 13’ from center of rear axle to farthest point forward including weights. Maximum of 6” tow-hook not included in 13’ length.