

# 9500 LIMITED PROSTOCK TRACTOR CLASS

## All Vehicles Must Conform to “General Vehicle Rules”

1. Weight Class is 9500 lbs.
2. Tires will be no wider than 25” or 38” maximum inside diameter.
3. “P” pumps and water injection allowed, no alcohol fuel
4. Exhaust will have four (4) 3/8 inch bolts, two (2) 1/2 inch bolts or a turbo containment device within 2” of cast turbo housing at 90-degree angles.
5. Tractor must use a Hart’s box turbo. Turbos will be ordered by MSTPA president and delivered to designated MSTPA board member where driver member will pick up and pay.
6. Must use steel fly wheel. Must have 6 strap clutch safety blankets and all safety equipment required as in the 9500 Profield Class.
7. Must have 3-way shut off.
8. All tractors will be equipped with a five-point harness and have a roll cage to meet the requirements of the class. (see General Rules section)
9. 9000 Profield Tractors may pull in the 9500 limited Prostock Tractor Class weighing 9700 lbs. but must follow rules for their 9000 Profield Class.
10. Tractors will be allowed to run 640 cubic inches. Billet head allowed. Recast or aftermarket heads will have port location same as stock and will have OEM manifold bolt pattern. (must be able to bolt on OEM manifold.
11. No intercoolers or ice boxes are allowed.
12. Deck plates allowed up to 1.00 thick.
13. Allow Superstock tractors to pull in the 9500 Limited Prostock Class weighing 8600 lbs.